


Thrust Cylindrical Roller Bearings



select	Inquiry	Designation	Principal dimensions(mm)				Basic load ratings(KN)		load limit(KN)		Mass(kg)
			d	d1	D	T	Cr	Cor	Cr	Cor	
89309	45		85	24	139	445	3600	0.615	□		
87409	45		100	25	154	560	3200	1.054	□		
81110	50		70	14	61	177	4000	0.14	□		
81210	50		78	22	117	315	3700	0.356	□		
89310	50		95	27	167	560	3200	0.887	□		
87410	50		110	27	200	740	2900	1.316	□		
89410	50		110	36	295	900	3000	1.316	□		
89410	50		110	31	295	900	3000	1.125	□		
81111	55		78	16	90	300	3600	0.218	□		
81211	55		90	25	154	405	3300	0.568	□		
89311	55		105	30	184	600	2900	1.18	□		
87411	55		120	29	222	870	2600	1.698	□		
81112	60		85	17	103	315	3300	0.266	□		
87212	60		95	26	172	480	3100	0.642	□		
89312	60		110	30	196	670	2700	1.26	□		
87412	60		130	32	260	1000	2500	2.26	□		
89412	60		130	42	390	1220	2500	2.818	□		
81113	65		90	18	107	340	3100	0.31	□		
81213	65		100	27	177	500	2900	0.721	□		
89313	65		115	30	194	670	2600	1.33	□		

Thrust Cylindrical Roller Bearings

89413	65		140	45	445	1410	2300		3.52	□
87413	65		140	34	300	1140	2300		2.75	□
81114	70		95	18	111	365	2900		0.332	□
81214	70		105	27	187	550	2700		0.768	□
89314	70		125	34	239	830	2400		1.82	□
87414	70		150	36	360	1380	2200		3.37	□
89414	70		150	48	450	1390	2100		4.38	□
81115	75		100	19	105	340	2700		0.393	□
81215	75		110	27	172	500	2600		0.8	□
89315	75		135	36	285	1010	2200		2.23	□