


High Speed-Precision ACBB



select	Inquiry	Designation	Principal dimensions(mm)			Basic load ratings(kN)		Limit Speed(r/min)		Mass(kg)	□15o				□25o			
			d	D	B	Cr	Cor	Grease	Oil		Limit Speed(r/min)	Basic load ratings(kN)	Limit Speed(r/min)	Basic load ratings(kN)	Cage			
										Oil	Grease	Cor	Cr	Oil	Grease	Cor	Cr	
71938 AC	190	260	33	146.7	187.2	4770	7200	3,65										
7038 CD	190	290	46	222.3	274.5	5040	8100	8,05										
7038 AC	190	290	46	210.6	261	3870	5670	9,5										
71940 ACD	200	280	38	179.1	225	4500	6750	5,1										
71940 AC	200	280	38	179.1	225	3870	5670	6,1										
7040 CD	200	310	51	266.4	351	4770	7200	10										
7040 AC	200	310	51	252.9	328.5	3600	5400	12,5										
71944 AC	220	300	38	187.2	256.5	4050	6030	5,55										
71944 CD	220	300	38	187.2	256.5	4050	6030	5,55										
7044 CD	220	340	56	304.2	409.5	4320	6750	13										
7044 AC	220	340	56	304.2	409.5	3600	5400	16										
71948 AC	240	320	38	194.4	274.5	3420	5040	6										
71948 CD	240	320	38	194.4	274.5	3420	5040	6										
7048 CD	240	360	56	310.5	441	3420	5040	17										
7048 AC	240	360	56	292.5	418.5	3060	4500	17										
71952 AC	260	360	46	238.5	360	3240	4770	10,5										
71952 CD	260	360	46	238.5	360	2520	3870	12										
7052 CD/P4A	260	400	65	374.4	567	3060	4770	25,5										
7052 AC	260	400	65	357.3	540	2700	4050	25,5										
71956 AC	280	380	46	248.4	387	2340	3600	13										
71956 CD/P4A	280	380	46	261.9	409.5	2880	4320	13										
71960 MA	300	420	56	333.9	540	3420	4770	19,5										
71960 CDM	300	420	56	333.9	540	2700	4050	23										

High Speed-Precision ACBB

71964 CD	320	440	56	339.3	558	2340	3870	24									
71964 M	320	440	56	339.3	558	3240	4500	20,5									
71968 CD	340	460	56	351	603	3060	4320	21,5									
71968 M	340	460	56	351	603	2160	3600	25,5									
71968 C	340	460	56	327.6	576	1800	2880	25,5									
71972 M	360	480	56	333.9	603	1710	2700	26,5									
706 CDP4	6	17	6	1.7255	0.6732	108000	163800	0,006									